

ULTRA WHITE
MATERIAL SAFETY DATA SHEET
1. Contact Information
Customer Service

JUSTICE PRODUCTS, LLC
 PO Box 10007
 Savannah, GA 31412
PHONE: (855) 720-2388
FAX: (912) 712-0204

Manufactured At

JUSTICE PRODUCTS, LLC
 2435 OLD 421 RD.
 STALEY, NC 27355
PLANT MANAGER: Mike Andrews
EMERGENCY PHONE: (855) 720-2388

2. Product Identification
Trade Name
ULTRA WHITE MARBLE
Common Name(s)

Ground Limestone

Chemical Formula
 $\text{CaCO}_3\text{MgCO}_5$
CAS Number

1317-65-3 (in TSCA Inventory)

Physical Form

irregular/angular particles, color varies: white, off-white

Particle Size

Size 0= 1/8"x10m; Size 1= 1/4"x1/8"; Size 2= 3/8"x1/4"

HMIS Ratings

| | |
|----------------------------|----------|
| HEALTH | 1 |
| FLAMMABILITY | 0 |
| REACTIVITY | 0 |
| PERSONAL PROTECTION | E |

3. Ingredients & Hazards

| Ingredient | Wt. % (Approx.) | CAS No. | OSHA PEL* | ACGIH TLV* |
|-----------------------------------|-----------------|------------|---|---------------------------------|
| Ground Limestone | > 99% | 1317-65-3 | 5 mg/m ³ Resp. 15 mg/m ³ Total | 2 mg/m ³ Resp. -- |
| Crystalline Silica, Quartz | 0.1% - 0.4% | 14808-60-7 | 0.1 mg/m ³ Resp. | 0.025 mg/m ³ Resp. |
| Water | < 1% | | | |

* Unless otherwise noted, all PEL and TLV values are reported as 8 hour time weighted averages (TWA).

4. Hazards Identification & Cautions

Appearance irregular/angular particles, color varies: white, off-white

Primary Routes of Entry skin contact, skin absorption, eye contact, ingestion.

Hazard Classification none (historical basis for classification)

Target Organs eye, skin and lungs

Medical Conditions Aggravated by Exposure

Skin contact may aggravate existing dermatitis.
 Breathing excessive quantities of ground limestone may aggravate pre-existing respiratory conditions.

Potential Health Effects

Eye Contact This product may produce irritation upon contact with the eye. *See also Section 4 below.*


Skin Contact Prolonged or repeated exposure may cause skin irritation. Ground limestone is not expected to be absorbed through the skin in harmful amounts or to produce an allergic skin reaction. *See also Section 4 below.*

Ingestion No adverse effect is expected. If ingested, seek medical advice. *See also Section 4 below.*

Inhalation Inhalation of excessive quantities of ground limestone dust may irritate the respiratory tract. *See also Section 4 below.*

Subchronic, Chronic None expected. No applicable information was found concerning any potential health effects resulting from Subchronic or chronic exposure to ground limestone.

This product typically contains crystalline silica (quartz sand) above 0.1% as naturally occurring impurity. The International Agency for Research on Cancer has concluded that "crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (group 1)." It is also noted that carcinogenicity was not detected in all industrial circumstance studies, and may be dependent on external factors affecting its biological activity or distribution of its polymorphs. (See IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 68 (1997).) Exposure to respirable silica has also been associated with silicosis, scleroderma, nephrotoxicity (see Occupational Lung Disorders, Third Edition, Chapter 12 (1994) and American Journal of Respiratory and Critical Care Medicine, Volume 155, pp 761-765 (1997).)

| 5. First Aid Measures | | | | | |
|--|--|------------|---|---|-------------------------------|
| Eye Contact | Follow good industrial hygiene practices. In case of contact, immediately flush eyes with plenty of water. Seek medical aid if necessary. | | | | |
| Skin Contact | Follow good industrial hygiene practices. Wash affected skin areas thoroughly with soap and water. Seek medical aid if necessary. | | | | |
| Inhalation | Follow good industrial hygiene practices. If excessive exposure by inhalation is suspected, remove to fresh air. If necessary, a MSHA/NIOSH or OSHA/NIOSH approved respirator is recommended. Seek medical aid if necessary. | | | | |
| Ingestion | Follow good industrial hygiene practices. If ingested, do not induce vomiting. If conscious, drink two glasses of water. Seek medical aid if necessary. | | | | |
| 6. Fire Fighting Measures | | | | | |
| Explosion Data | Not Explosive | | NFPA 704M Hazard Classification Use Appropriate extinguishing media for packaging material if applicable.  | | |
| LEL | Not Applicable | | | | |
| UEL | Not Applicable | | | | |
| Flammability | Not Flammable or Combustible | | | | |
| Extinguishing Media | Product will not burn. | | | | |
| Flammability | Not Flammable or Combustible | | | | |
| Flash Point | Not Applicable | | | | |
| Auto-Ignition | Not Applicable | | | | |
| 7. Accidental Release Measures | | | | | |
| Vacuum, pump or scoop spilled material into containers for reclaiming or disposal. Use proper respiratory and personal protective equipment. MSHA/NIOSH or OSHA/NIOSH approved respirator recommended. Spilled materials may cause slippery conditions when wet. Care should be exercised when walking on spills on floors or concrete pads. No neutralizing chemicals required. Material is inert and noncreative. Ground limestone is not a CERCLA listed hazardous substance. | | | | | |
| 8. Handling & Storage | | | | | |
| Storage in a cool, dry location is recommended. Keep away from acids. Spilled materials may cause slippery conditions when wet. Care should be exercised when walking on spills on floors or concrete pads. | | | | | |
| Minimize dust generation and accumulation. If excessive dust is generated, provide adequate ventilation and use proper respiratory and personal protective equipment. MSHA/NIOSH or OSHA/NIOSH approved respirator recommended. | | | | | |
| 9. Exposure Control / Personal Protection | | | | | |
| Hazardous Ingredient | Wt. % (Approx.) | CAS No. | MSHA PEL* | OSHA PEL* | ACGIH TLV* |
| Ground Limestone | > 99% | 1317-65-3 | 10 mg/m ³ Total | 15 mg/m ³ Total 5 mg/m ³ Resp. | 2 mg/m ³ Resp. |
| Crystalline Silica | 0.1% - 0.4% | 14808-60-7 | 5 mg/m ³ Resp. | 0.1 mg/m ³ Resp. | 0.025 mg/m ³ Resp. |
| * Unless otherwise noted, all PEL and TLV values are reported as 8 hour time weighted averages (TWA). | | | | | |
| Respiratory Protection | If respirator is required, use of MSHA/NIOSH or OSHA/NIOSH approved respirator is recommended. | | | | |
| Ventilation | Use exhaust ventilation, if required, to maintain dust concentration below recommended exposure limits. | | | | |
| Protective Equipment | Wear side shield safety glasses. Rubber gloves are recommended for prolonged exposure. | | | | |
| 10. Physical & Chemical Properties | | | | | |
| Physical State | Solid | | Boiling Point | Not Applicable | |
| Appearance & Odor | Odorless, irregular/angular particles, color varies: white, off-white, light gray | | Freezing Point | Not Applicable | |
| pH (Aqueous Suspension) | 9 - 10 | | Vapor Pressure | Not Applicable | |
| Specific Gravity | ~2.7 | | Vapor Density | Not Applicable | |
| % Solubility in Water: | 1.4 mg/100 ml @ 25°C | | VOC | None | |
| Melting Point | 825°C | | Evaporation Rate | Not Applicable | |

| 11. Stability & Reactivity | | | | |
|---|---|----------|---|------------|
| Chemically stable? | Yes | | | |
| Compatible with other substances? | Yes (see below) | | | |
| Hazardous Decomposition/By-Products | No hazardous decomposition or by-products expected. | | | |
| Conditions Contributing to Hazardous Polymerization | None, inert and nonreactive. | | | |
| Incompatibility (Materials to Avoid) | Will react with acids to produce carbon dioxide gases. | | | |
| 12. Disposal Considerations | | | | |
| EPA Waste Number | Under RCRA (40 CFR 261) ground limestone is a non-hazardous waste. Dispose of waste material in accordance with all local state and federal requirements. | | | |
| 13. Toxicological Information | | | | |
| Ground Limestone | CAS No. 1317-65-3 | | | |
| Primary Route of Exposure | Skin, Eye Contact, Inhalation, Ingestion | | | |
| Acute Health Hazards | | | | |
| Eye Contact | Eye contact may cause mechanical irritation. Calcium carbonate is a severe eye irritant*. | | | |
| Skin Contact | Skin contact may aggravate existing dermatitis. Calcium carbonate is a moderate skin irritant*. | | | |
| Inhalation | Inhalation from prolonged and continuous exposure to excessive quantities of dust may aggravate existing respiratory conditions. | | | |
| * Calcium carbonate ORAL LD(50) in rats is 6,450 mg/kg. | | | | |
| Chronic Health Hazards* | | | | |
| Carcinogenicity* | NTP? No | IARC? No | OSHA? No | |
| Mutagenicity | None known | | | |
| Teratogenicity | None known | | | |
| Reproductive Effects | None known | | | |
| * Dangerous Properties of Industrial Materials, 7 th Edition, pp 667, Sax and Lewis 1989 | | | | |
| * See Section 3 for discussion of crystalline silica. | | | | |
| 14. Transport Information | | | | |
| EPA Waste Number | Not regulated | | | |
| DOT Classification | Not regulated | | | |
| DOT/IMO Classification | Not regulated | | | |
| Internal UN | Not regulated | | | |
| 15. Regulatory Information | | | | |
| SARA Title III Section 302 Extremely Hazardous Substances | | | | |
| This product does not contain extremely hazardous substances subject to the reporting requirements of Section 302 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 355. | | | | |
| SARA Title III Section 311 and 312 Health and Physical Hazard Categories per 40 CFR 370.2: | | | | |
| Immediate | Delayed | Fire | Pressure | Reactivity |
| Yes | Yes | No | Yes | Yes |
| SARA Section 313 Notification | | | TSCA | |
| This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 | | | Product is listed by the Initial Inventory, Vol. 1, Appendix A, CAS No. 1317-65-3 | |

The international Agency for Research on Cancer has concluded that "crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1)." It also noted that carcinogenicity was not detected in all industrial circumstance studies, and may be dependent on external factors affecting its biological activity or distribution of its polymorphs. (See IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 68 (1997).) Exposure to respirable silica has also been associated with silicosis, scleroderma, and nephrotoxicity (see Occupational Lung Disorders, Third Edition, Chapter 12 (1994) and American Journal of Respiratory and Critical Care Medicine, Volume 155, pp 761-765 (1997).)

WARNING

This product may also contain extremely small amounts of one or more naturally occurring materials known to the State of California to cause cancer, birth defects, or other reproductive harm.

16. Other Information

Disclaimer of Liability

Justice Products, LLC believes the information contained herein is accurate; however, Justice Products, LLC makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein by any party. The provision of the information contained herein is not intended to be and should not be construed as legal advice or as ensuring compliance with federal, state or local laws and regulations. Any party using this product should review all such laws, rules and regulations prior to use.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OR MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.

JUSTICE PRODUCTS, LLC

PO Box 10007
Savannah, GA 31412

Plant Manager: Mike Andrews
Emergency Phone: (855) 720-2388

Date Prepared
July 27, 1982

Last Revised
April 21, 2011

LAST PAGE